

APPLICATION FOR
UNITED STATES LETTERS PATENT

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

Be it known that I, Robin A. Adair, a citizen of the United States of America, and resident of the State of California, having a postal address of 4340 Jan Drive, Carmichael, California, 95608, have invented a new and useful "**Fence Guard Construction**", of which the following forms the specification.

"Fence Guard Construction"

BACKGROUND OF THE INVENTION

CROSS REFERENCE TO RELATED APPLICATIONS

Not applicable.

5 Field of the Invention

The present invention relates to the field of fence guards for inhibiting the growth of vegetation beneath and adjacent to a fence line and in particular to a new type of fence guard having a unique anchoring arrangement.

Description of Related Art

10 As can be seen by reference to the following U.S. Patent Nos. 4,349,989; 3,768,780; 5,317,833; and, 6,561,491, the prior art is replete with myriad and diverse fence guard constructions used to prevent grass and weeds from growing under and/or adjacent to a fence line.

15 While all of the aforementioned prior art constructions are more than adequate for the basic purpose and function for which they have been specifically designed, they are uniformly deficient with respect to their failure to provide a simple, efficient, and practical fence guard construction that not only has an enhanced aesthetic appearance, but which also has an improved and unobtrusive anchoring arrangement for attaching the fence guard construction to the fence posts.

As anyone who has a fence surrounding their property is all too well aware, the difficulty in maintaining a well manicured lawn in the vicinity of the fence line is the biggest problem associated with a fence.

5 As a consequence of the foregoing situation, there has existed a longstanding need among property owners for a new and improved fence guard construction having an improved decorative appearance and a unique anchoring arrangement; and, the provision of such a construction is the stated objective of the present invention.

BRIEF SUMMARY OF THE INVENTION

10 Briefly stated, the fence guard construction that forms the basis of the present invention comprises in general a pair of end cap members and a plurality of intermediate segments which all share some of the same structural characteristics, as well as, a generally similar external appearance.

15 As will be explained in greater detail further on in the specification, the fence guard construction includes a proximal end cap member adapted to releasably receive the first of a series of identical intermediate segments that are adapted to interlock with one another.

20 In addition, a distal end cap member is virtually a mirror image of the proximal end cap member with the exception of a mounting flange formed on the open end of the distal end cap member wherein, the mounting flange is adapted to releasably engage the distal end of the last of the identical intermediate segments.

Furthermore, both of the end cap members and the intermediate segments are provided with both vertically and horizontally aligned mounting flanges that allow the fence guard construction to be affixed both to a plurality of fence posts, as well as, anchored to the ground adjacent to the fence line.

25 BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

These and other attributes of the invention will become more clear upon a thorough study of the following description of the best mode for carrying out the invention, particularly when reviewed in conjunction with the drawings, wherein:

30 FIG. 1 is a perspective view of a fence line provided with the fence guard construction that forms the basis of the present invention;

FIG. 2 is a top plan view of a representative fence guard construction;

FIG. 3 is a perspective view of the proximal end cap member;
FIG. 4 is an enlarged detail view of the circled portion of Fig. 3;
FIG. 5 is a cross-sectional view taken through line 5-5 of Fig. 4; and,
FIG. 6 is a detail view showing the typical flanged engagement between the
5 distal end cap member, the intermediate segments, and the proximal end cap
member.

DETAILED DESCRIPTION OF THE INVENTION

As can be seen by reference to the drawings, and in particular to FIG. 1, the
fence guard construction that forms the basis of the present invention is designated
10 generally by the reference number **10**. The construction **10** comprises a proximal end
cap member **20**, a plurality of intermediate segments **30** and a distal end cap member
40. These structural elements will now be described in seriatim fashion.

As can best be seen by reference to Fig. 3, the proximal end cap member **20**
comprises a hollow elongated rectangular body **21** preferably fabricated from plastic
15 and having an open distal end (not shown) and a closed proximal end **22** wherein, the
external surfaces **24** of the hollow body **21** are further provided with a simulated brick
appearance.

Turning now to Figs. 1,2, and 6, it can be seen that the plurality of intermediate
segments **30** each comprises an open ended hollow elongated rectangular body **31**
20 wherein, the external surfaces **34** of the hollow bodies **31** are all provided with a
simulated brick appearance and the proximal end of each of the intermediate
segments **30** is provided with a connector flange **33** that is dimensioned to engage the
distal end of each of the other intermediate segments **30**, as well as, the distal end of
the proximal end cap member **20**.

As can also be appreciated by reference to Figs. 1,2, and 6, the distal end cap
member **40** comprises a hollow elongated rectangular body **41** having a closed distal
end **42** wherein, the open proximal end of the body **41** is provided with a connector
flange **43** adapted to engage the distal end of any of the intermediate segments **30**.

Turning now to Figs. 3 through 5, it can be seen that each of the end cap
30 members **20 40**, as well as, the intermediate segments **30 30** is provided with both
horizontal **50** and vertical **60** apertured mounting flanges wherein, the horizontal

mounting flanges **50** extend outwardly from the bottom of the cap members **20 40**, as well as, the segments **30** and are dimensioned to receive an elongated ground penetrating spike **70**.

5 Furthermore, the vertical mounting flanges **60** are formed in the rear wall of the end cap members **20 40** and the segments **30** at the terminus of a semi-conical recess **61** formed on the top surface of each end cap member **20 40** and segment **30** wherein, the vertical mounting flanges **60** are dimensioned to receive conventional fasteners **80** for securing the end cap members **20 40** and the segments **30** to spaced fence posts **101** along a fence line **100**.

10 Turning now to Fig. 6, it can also be seen that a plurality of discrete apertures **81** may be formed in the mating surfaces of the fence guard construction **10**, wherein, the apertures **81** are dimensioned to receive conventional fasteners **80** for fixedly securing the mating components together in a well recognized fashion.

15 Although only an exemplary embodiment of the invention has been described in detail above, those skilled in the art will readily appreciate that many modifications are possible without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the following claims.

20 Having thereby described the subject matter of the present invention, it should be apparent that many substitutions, modifications, and variations of the invention are possible in light of the above teachings. It is therefore to be understood that the invention as taught and described herein is only to be limited to the extent of the breadth and scope of the appended claims.